



## Product Data Sheet



# Ralston Solvent Industrial High-Gloss

### Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle  
P.O. Box 205 - 8000 AE Zwolle  
The Netherlands  
T +31 38 429 11 00  
F +31 38 421 04 14  
E [info@ralstoncolour.com](mailto:info@ralstoncolour.com)  
I [www.ralstoncolour.com](http://www.ralstoncolour.com)

### Description

Scratch-resistant, high-gloss, anticorrosive pre-coat and finishing enamel based on urethane/alkyd resin.

### Application

Exterior and interior, as a pre-coat and finishing enamel on pre-treated metal.

### Principal characteristics

- scratch and impact resistant
- anticorrosive
- good outdoor durability
- easy to apply
- excellent flow with low propensity to run and good (edge) coverage

### Colour and gloss

All colours available through the Ralston ALK tinting system

High-gloss

Paints based on alkyd resin have a tendency to yellow particularly in areas that are not exposed to UV light. Our Ralston Aqua paints are a non-yellowing alternative for indoor use.

### Basic data

#### At 20°C and 65% R.H.

Density:	approx. 1.1 kg/dm <sup>3</sup>
Viscosity:	approx. 90 K.U.
Solids content:	approx. 52 volume %
Dust-dry:	approx. 2.5 hours
Tack-free:	approx. 3.5 hours
Recoatable:	approx. 16 hours

*N.B.: Drying times mentioned are averages and dependent on weather conditions and colour. For darker colours, longer drying times apply at lower temperatures than for white and light colours.*

### Spreading Rate

#### Film thickness

35 microns dry (approx. 67 microns wet)

#### Theoretical spreading rate

At 35 microns dry film thickness: 14.9 m<sup>2</sup>/l

#### Practical spreading rate

Dependent on surface and application method 60-85% of the theoretical spreading rate.



## Product Data Sheet

### Ralston Solvent Industrial High-Gloss (continued)

#### Application conditions

- Ambient temperature: min. 5°C
- Surface temperature: min. 3°C above dew point
- Relative humidity: max. 85%

#### Instructions for use

- Stir well before use
- Dilution: ready to use, slightly dilute with white spirit if desired
- Clean tools with white spirit

#### Product details

- Package: 1 and 2.5 liter – BW and BTR
- Storage: in unopened, original package at a cool, dry and frost-proof area
- Maximum usage period: 12 months

#### Environment and health

- Flash point: 39°C
- Safety regulations: National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.

N.B.: Characteristics and technical data are dependent on the colour. Values mentioned are averages.

- BW = Base White
- BTR = Base Transparent
- W = White

