



## Product Data Sheet



# Ralston Satintex

### Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle  
P.O. Box 205 - 8000 AE Zwolle  
The Netherlands  
T +31 38 429 11 00  
F +31 38 421 04 14  
E [info@ralstoncolour.com](mailto:info@ralstoncolour.com)  
I [www.ralstoncolour.com](http://www.ralstoncolour.com)

### Description

Superb, exceptionally good covering, semi-mat, scrub resistant, water-based wall paint based on acrylic dispersion. For interior use.

### Application

On indoor stony surfaces such as concrete, masonry, plaster, sheet material and glass fibre.

### Principal characteristics

- Good hiding power
- Very easy to clean
- Easy to apply
- Unseparable

### Colour and gloss

White, other colours through the Ralston AQ tinting system.

Semi mat, low satin gloss

### Technical data

#### At 20°C and 65% R.H.

Density:	approx. 1.35 kg/dm <sup>3</sup>
Viscosity:	approx. 125 K.U.
Solids content:	approx. 45 volume %
Dust-dry:	approx. 2 hours
Recoatible:	approx. 8-10 hours
Scrub resistance:	Class 1, according to DIN EN 13 300 (after 1 month)
Application:	Brush, roller and/or airless spray
Spraying data:	<b>Airless Spray</b>

Pressure: 11-13 MPa (110-130 bar)  
Nozzle: 0.018-0.021 inch (0.46-0.53 mm)  
Dilution: approx. 5% water

Surface condition:

#### Untreated surfaces:

Should be air-dried, fixed, clean and free from dust, grease and cement skin.

#### Treated surfaces:

Should be fixed, clean and free from grease and dust.

#### NB:

Cement-bound surfaces should be approx. 28 days old. Pre-treat absorbing, porous surfaces (locally) with Ralston Wall Primer or Ralston ColourPrime.



## Product Data Sheet

### Ralston Satintex (continued)

#### Spreading rate

##### *Practical spreading rate*

6-8 m<sup>2</sup>/l rolled, dependent on the porosity and structure of the surface. Apply on a test panel if necessary.

#### Application conditions

- Ambient and surface temperature: min. 8°C
- Relative humidity: max. 85%

#### Instructions for use

- Stir well before use
- Dilution: ready to use, water if desired
- Clean tools with water

#### Product details

Package:	1, 2.5 and 10 liter – BW and BTR 10 liter - W
Storage:	in unopened, original package at a cool, dry and frost-proof area
Maximum usage period:	12 months

#### Environment and health

Flash point:	none
Safety regulations:	National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.

N.B.: Characteristics and technical data are dependent on the colour. Values mentioned are averages.

BW = Base White  
BTR = Base Transparent  
W = White