



## Product Data Sheet



# Ralston ExtraMat

### Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle  
P.O. Box 205 - 8000 AE Zwolle  
The Netherlands  
T +31 38 429 11 00  
F +31 38 421 04 14  
E info@ralstoncolour.com  
I www.ralstoncolour.com

### Description

Superb, exceptionally good covering, fully mat, lap free, water-based wall paint based on acrylic dispersion. Excellent scrub resistance. For interior use.

### Application

On interior stony surfaces such as concrete, masonry, plaster, sheet material and glass fiber.

### Principal characteristics

- Full mat
- Lap free
- Easy to clean
- Excellent application properties

### Colour and gloss

Colours through the Ralston AQ tinting system.

Full Mat

### Technical data

#### At 20°C and 65% R.H.

Density:	approx. 1.5 kg/dm <sup>3</sup>
Viscosity:	approx. 120 K.U.
Solids content:	approx. 45 volume %
Dust-dry:	approx. 1 hour
Recoatable:	approx. 6 hours
Scrub resistance:	Class 1, according to DIN EN 13 300 (after 1 month)
Application:	Brush, roller or airless spray
Spray data:	<b>Airless spray</b> Pressure: 11-15 MPa (110-150 bar) Nozzle: 0.018-0.021 inch (0.46-0.53 mm) Dilution: approx. 5% water

#### Surface condition:

#### Untreated surfaces:

The surface must be free from grease and dust. Remove possible cement skin from concrete; pre-treat chalking and/or absorbing surfaces with Ralston Wall Primer or Ralston ColourPrime. Apply one or two opaque coats of Ralston ExtraMat.

#### Treated surfaces:

Clean and make free from grease and dust; repair where necessary; treat with Ralston ExtraMat for an opaque finish.



## Product Data Sheet

### Ralston ExtraMat (continued)

#### Glass fibre wallpaper:

Glass fibre wallpaper should be applied as instructed (allow sufficient drying time for glass fibre adhesive); apply two coats of Ralston ExtraMat.

#### Spreading rate

*Practical spreading rate*

6-9 m<sup>2</sup>/l rolled, dependent on the porosity and structure of the surface. Apply on a test panel if necessary.

#### Application conditions

- Ambient and surface temperature: min. 8°C
- Relative humidity: max. 85%

#### Instructions for use

- Stir well before use
- Dilution: ready to use, water if desired
- Clean tools with water

#### Product details

Package:	1, 2.5 and 10 liter – BW and BTR 2.5 and 10 liter - W
Storage:	in unopened, original package at a cool, dry and frost-proof area
Maximum usage period:	12 months

#### Environment and health

Flash point:	none
Safety regulations:	National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.

N.B.: Characteristics and technical data are dependent on the colour. Values mentioned are averages.

BW = Base White  
BTR = Base Transparent  
W = White