



Product Data Sheet



Ralston ColourPrime

Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle
P.O. Box 205 - 8000 AE Zwolle
The Netherlands
T +31 38 429 11 00
F +31 38 421 04 14
E info@ralstoncolour.com
I www.ralstoncolour.com

Description

Colourable, opaque wall primer for absorbing and porous substrates such as plasterboard, concrete, masonry and plasterwork. For interior use.

Application

As a primer sealer on absorbing and porous surfaces and on concrete, masonry and plasterwork, wooden and stony sheet materials for interior use.

Principal characteristics

- Quick drying
- Reduces absorption and powdering of the substrate
- Improves adhesion of the paint system
- Good hiding power in combination with the top coat

Colour and gloss

All colours available through the Ralston AQ tinting system

Technical data

At 20°C and 65% R.H.

Density:	approx. 1.35 kg/dm ³
Viscosity:	approx. 105 K.U.
Solids content:	approx. 39 volume %
Dust-dry:	approx. 1 hour
Recoatible:	approx. 4-6 hours
Application:	long brush, roller
Surface conditions:	The surface should be air-dried, fixed, clean and free from dust, grease and cement skin.

Spreading rate

Practical spreading rate

9 m²/l rolled, dependent on the porosity and structure of the surface. Apply on a test panel if necessary.



Product Data Sheet

Ralston ColourPrime (continued)

Application conditions

- Ambient and surface temperature: min. 10°C
- Relative humidity: max. 85%

Instructions for use

- Stir well before use
- Dilution: ready to use
- Clean tools with water

Product details

- Package: 2.5 and 10 liter – BW and BTR
Storage: in unopened, original package at a cool, dry and frost-proof area
Maximum usage period: 12 months

Environment and health

- Flash point: none
Safety regulations: National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.

N.B.: Characteristics and technical data are dependent on the colour. Values mentioned are averages.

- BW = Base White
BTR = Base Transparent
W = White