



Product Data Sheet



Ralston Wall Primer

Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle
P.O. Box 205 - 8000 AE Zwolle
The Netherlands
T +31 38 429 11 00
F +31 38 421 04 14
E info@ralstoncolour.com
I www.ralstoncolour.com

Description

Good penetrating colourless sealer for interior and exterior use.

Application

As a primer sealer on absorbing and porous stony surfaces such as concrete, masonry, plasterwork and stony sheet work etc., for interior and exterior use. As undercoat for acrylate dispersion wall paints. Can also be mixed with Ralston acrylate dispersion wall paints.

Principal characteristics

- Reduces absorption of the substrate
- Improves adhesion
- Quick drying
- Water vapour permeable

Colour and gloss

Colourless (in package milky white)

Mat (if sufficiently absorbed)

Technical data

At 20°C and 65% R.H.

Density:	approx. 1.0 kg/dm ³
Viscosity:	approx. 75 K.U.
Solids content:	approx. 19 volume %
Dust-dry:	approx. 1 hour
Recoatable:	approx. after 4 hours
Application:	Brush, roller

Allow product to be absorbed well into the substrate and avoid the formation of superficial shiny areas!

Surface condition: The surface must be air-dried, fixed, clean and free from dust, grease and cement skin.

NB:

Cement-bound surfaces should be ± 28 days old.

Spreading rate

Practical spreading rate

3-5 m²/l, dependent on the porosity and structure of the surface. Apply on a test panel if necessary.



Product Data Sheet

Ralston Wall Primer (continued)

Application conditions

- Ambient and surface temperature: min. 10°C
- Relative humidity: max. 85%

Instructions for use

- Stir well before use
- Dilution: ready to use
- Clean tools with water

Product details

- Package: 1 and 5 liter
- Storage: in unopened, original package at a cool, dry and frost-proof area
- Maximum usage period: 12 months

Environment and health

- Flash point: none
- Safety regulations: National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.