



## Product Data Sheet



# Ralston Latex

### Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle  
P.O. Box 205 - 8000 AE Zwolle  
The Netherlands  
T +31 38 429 11 00  
F +31 38 421 04 14  
E info@ralstoncolour.com  
I www.ralstoncolour.com

#### Description

Good covering, breathing, water-based wall paint based on acrylic dispersion. For interior use.

#### Application

On concrete, plasterwork, masonry and stony sheet work, interior.

#### Principal characteristics

- Easy to apply
- Good hiding power
- High water vapour permeability

#### Colour and gloss

White

Mat

#### Technical data

##### At 20°C and 65% R.H.

Density:	approx. 1.5 kg/dm <sup>3</sup>
Viscosity:	approx. 125 K.U.
Solids content:	approx. 35 volume %
Dust-dry:	approx. 1 hour
Recoatable:	approx. 6-8 hours
Wet rub resistance:	Class 3, according to DIN EN 13 300 (after 1 month)
Application:	Brush, roller, (airless) spray
Spraying data:	<b>Airless spray</b> Pressure: 11-13MPa (110-130 bar) Nozzle: 0.018-0.021 inch (0.46-0.53 mm) Thinner: ca. 5% water

#### Surface condition:

##### **Untreated surfaces (air-dried):**

- Remove dust and grease and possible cement-skin from concrete;
- Pre-treat powdering and/or absorbing surfaces with Ralston Wall Primer or Ralston ColourPrime. Apply one or two (hiding) coats of Ralston Latex.

##### **Existing (dispersion) wall paint surfaces:**

- Clean the surface and remove dust and grease;
- Repair if necessary;
- Apply one or two (hiding) coats of Ralston Latex.



## Product Data Sheet

### Ralston Latex (continued)

#### Spreading rate

##### *Practical spreading rate*

6-8 m<sup>2</sup>/l rolled, dependent on the porosity and structure of the surface. Apply on a test panel if necessary.

#### Application conditions

- Ambient and surface temperature: min. 10°C
- Relative humidity: max. 85%

#### Instructions for use

- Stir well before use
- Dilution: ready to use, water if desired
- Clean tools with water

#### Product details

- Package: 2.5 and 10 liter – W
- Storage: in unopened, original package at a cool, dry and frost-proof area
- Maximum usage period: 12 months

#### Environment and health

- Flash point: none
- Safety regulations: National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.