



Product Data Sheet



Ralston Siloxan Primer

Ralston Colour & Coatings B.V.

Russenweg 14 - 8041 AL Zwolle
P.O. Box 205 - 8000 AE Zwolle
The Netherlands
T +31 38 429 11 00
F +31 38 421 04 14
E info@ralstoncolour.com
I www.ralstoncolour.com

Description

Special, colourless sealer, excellent penetrating and vapour permeable. For exterior use.

Application

As primer sealer on absorbing, porous, exterior, stony surfaces such as concrete, masonry and plaster that will be finished with Ralston Siloxan Mat. In case of very strong absorbing substrates, the application can be repeated wet-in-wet.

Principal characteristics

- Reduces absorption of the surface
- Improves adhesion
- No unpleasant odour
- Quick drying
- Water vapour permeable
- Alkali resistant

Colour and gloss

Colourless (in package milky white)

Mat (if sufficiently absorbed)

Technical data

At 20°C and 65% R.H.

Density:	approx. 1.0 kg/dm ³
Viscosity:	low viscous
Solids content:	approx. 13 volume %
Dust-dry:	approx. 1 hour
Recoatable:	approx. after 3 hours
Application:	Long brush
Surface condition:	Surface should be air-dried, fixed, clean and free from dust, grease and cement skin.

NB: Cement-bound surfaces should be ± 28 days old.

Spreading rate

Practical spreading rate

3-7 m²/l dependent on the porosity and structure of the surface. Apply on a test panel if necessary.



Product Data Sheet

Ralston Siloxan Primer (continued)

Application conditions

- Ambient and surface temperature: min. 10°C
- Relative humidity: max. 85%

Instructions for use

- Stir well before use
- Dilution: ready to use
- Clean tools with water

Product details

- Package: 5 liter
- Storage: in unopened, original package at a cool, dry and frost-proof area
- Maximum usage period: 12 months

Environment and health

- Flash point: none
- Safety regulations: National legislation regarding safety, health and environment applies to users. For more information and current data, see the latest version of the Material Safety Data Sheet.