Ralston 1 pot system

Moisture regulating, satin-gloss opaque stain, which can be used as a basecoat, undercoat and topcoat

• Ralston 3-in-1 Satin





• paint • passion • people

3-in-1 Satin (1 pot system)

The Ralston 3-in-1 Satin is a moisture-regulating, satin-gloss opaque stain which can be used as a base coat, undercoat and top coat on a variety of timber.





Ralston 3-in-1 Satin

- Primer and top coat in one
 Easy to apply
- Easy to applyGood moisture regulation
- Highly elasticity

Intended Use

On front joinery (e.g. as a one-pot-system), for both new and existing woodwork. Can also be applied over the existing traditional paintwork (after cleaning and sanding the surface).

	Ralston 3-in-1 Satin
Theoretical Coverage *	14,7 m2/l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	2,5
Tack-Free Time **	5
Time To Recoat **	18
Wet Film Thickness	68 Mµ
Dry Film Thickness	45 Mµ
Gloss Level	Satin gloss, approx. 42 G.U. at 60 °

* Depends on application method, applied wet film thickness and surface

** Drying time in hours

Paints based on alkyd resin have atendency to yellow particularly in areas that are not exposed to UV light (interior paintwork). Our Ralston Aqua paints are a non-yellowing alternative for indoor use.

For more information visit www.ralstoncolour.com

Part of Royal Van Wijhe Verf Ralston COLOUR & COATINGS

Ralston Colour & Coatings B.V. Postbus 205, 8000 AE Zwolle Nederland +31(0)38 - 429 11 00 info@ralstoncolour.com www.ralstoncolour.com