## **Ralston 4S enamels**

Four seasons outdoor painting

- Ralston 4S Satin
- Ralston 4S High-Gloss






• paint • passion • people

## 4S High-Gloss & 4S Satin

The Ralston 4S system, due to its optimal fluid and paint drying system, is easy to apply throughout the year and gives excellent results. A complete system that extends the outdoor painting season to all four seasons.



Red AS Satin	<ul> <li>Ralston 4S Satin</li> <li>Can be applied year-round '4 seasons'</li> <li>Good outdoor durability</li> <li>Fast initial drying</li> <li>Good (edge)coverage</li> </ul>
Exterior	Intended Use As finishing coat on pre-treated woo metal and plastic.
Red AS High-Gloss	<ul> <li>Ralston 4S High-Gloss</li> <li>Can be applied year-round '4 seasons'</li> <li>Good outdoor durability</li> <li>Fast initial drying</li> <li>Good (edge)coverage</li> </ul>
Exterior	Intended Use As finishing coat on pre-treated woo

**-**1

ood,

As finishing coat on pre-treated wood, metal and plastic.

	Ralston 45 Satin
Theoretical Coverage *	16 m2/l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	2,5
Tack-Free Time **	4
Time To Recoat **	18
Wet Film Thickness	70 Μμ
Dry Film Thickness	40 Mµ
Gloss Level	Satin gloss, approx. 35 G.U. at 60 °

	Ralston 4S High-Gloss
Theoretical Coverage *	16,8 m2/l
Drying Time Condition	20 °C / 65 % R.H.
Dust-Free Drying Time **	2,5
Tack-Free Time **	4
Time To Recoat **	18
Wet Film Thickness	60 Mµ
Dry Film Thickness	40 Mµ
Gloss Level	High gloss, approx. 80 G.U. at 60 °

Depends on application method, applied wet film thickness and surface

\*\* Drying time in hours

For more information visit www.ralstoncolour.com

Part of Royal Van Wijhe Verf



Ralston Colour & Coatings B.V. Postbus 205, 8000 AE Zwolle Nederland

+31(0)38 - 429 11 00 info@ralstoncolour.com www.ralstoncolour.com