

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

1 Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** Ralston 4S Wood-Primer BTR**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture Paint**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

2 Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS08

Signal word Warning**Hazard-determining components of labelling:**

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements

H226 Flammable liquid and vapour.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

Dangerous components:		
CAS: 1317-65-3 EINECS: 215-279-6	Limestone (calcium carbonate) substance with a Community workplace exposure limit	>10–≤25%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) substance with a Community workplace exposure limit	>2.5–≤25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336, EUH066	>2.5–≤10%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg ₃ H ₂ (SiO ₃) ₄) substance with a Community workplace exposure limit	>2.5–≤10%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336, EUH066	>2.5–<10%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) fine fraction of crystalline silica ⚠ STOT RE 1, H372	>2.5–<10%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Asp. Tox. 1, H304, EUH066	≥0–≤2.5%
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg.nr.: 01-2119539582-35	2-methylpentane-2,4-diol ⚠ Repr. 2, H361d; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures
General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 2)

Consult doctor if symptoms persist.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Take off contaminated clothing.

Wash with water and soap.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Observe instructions for use / storage.

Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight.

Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1317-65-3 Limestone (calcium carbonate)

WGW (Netherlands)	Long-term value: 10 mg/m ³ zie bijl. 3
-------------------	--

14808-60-7 Quartz (SiO₂)

BOELV (EU)	Long-term value: 0.1* mg/m ³ *respirable fraction
WGW (Netherlands)	Long-term value: 0.075 mg/m ³ respirabele fractie

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

WGW (Netherlands)	Long-term value: 0.25 mg/m ³ respirabel
-------------------	---

DNELs

Hydrocarbons, C₉-C₁₁, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)
Dermal	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers) 208 mg/kg bw/24h (Workers)
Inhalative	DNEL Systemic; Long term	185 mg/m ³ (Consumers) 871 mg/m ³ (Workers)

Hydrocarbons, C₉-C₁₂, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral	DNEL Systemic; Long term	26 mg/kg bw/24h (Consumers)
------	--------------------------	-----------------------------

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 4)

Dermal	DNEL Systemic; Long term	26 mg/kg bw/24h (Consumers) 44 mg/kg bw/24h (Workers)
Inhalative	DNEL Systemic; Long term	71 mg/m ³ (Consumers) 330 mg/m ³ (Workers)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

Hand protection



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection



Tightly sealed goggles

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

Different according to colouring

Odour:

Product specific

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

154–193 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Flammability

Flammable.

Lower and upper explosion limit

Lower:

Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 5)

Upper:	Not determined.
Flash point:	52 °C
Auto-ignition temperature:	>200 °C (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	1,141.3–1,351.55 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	2 hPa (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Density and/or relative density	
Density at 20 °C:	1.3–1.34 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Viscous
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	18.95 %
Solids content:	81.1 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Flammable liquids	Flammable liquid and vapour.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Oxidising substances.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 6)

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

1317-65-3 Limestone (calcium carbonate)

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral	LD50	>15,000 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	13.1 mg/l (rat)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)

107-41-5 2-methylpentane-2,4-diol

Oral	LD50	3,700 mg/kg (rat)
Dermal	LD50	8,560 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:

1317-65-3 Limestone (calcium carbonate)

EC50	>1,000 mg/l /48h (daphnia)
	>200 mg/l /72h (Desmodesmus subspicatus)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 7)

LC50	>10,000 mg/l /96h (Oncorhynchus mykiss)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
EL0	1,000 mg/l /48h (daphnia)
EL50	>1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL50	>1,000 mg/l /96h (Oncorhynchus mykiss)
NOELR	100 mg/l /72h (Pseudokirchneriella subcapitata)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
EL50	4.6–10 mg/l /72h (Pseudokirchneriella subcapitata)
	10–22 mg/l /48h (daphnia)
LL50	10–30 mg/l /96h (Oncorhynchus mykiss)
LOEC	0.203 mg/l /21d (daphnia)
NOEC	0.097 mg/l /21d (daphnia)
NOELR	1 mg/l /72h (algae)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL0	1,000 mg/l /96h (Oncorhynchus mykiss)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects
Remark: Harmful to fish

Additional ecological information:
General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

13.1 Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 8)

HP14	Ecotoxic
------	----------

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

UN1263 PAINT

IMDG

PAINT

IATA

Paint

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number:

F-E, S-E

Stowage Category

A

14.7 Maritime transport in bulk according to

IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

D/E

Remarks:

Exempted according to 2.2.3.1.5 (Viscous liquids)

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 1263 PAINT, 3, III

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 9)

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior/exterior trim and cladding paints for wood and metal
- Solvent-borne coatings, Limit value: 300 g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.10.2023

Version number 1.00

Revision: 24.10.2023

Trade name: Ralston 4S Wood-Primer BTR

(Contd. of page 10)

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3