Revision: 08.10.2025



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025

Version number 2.00 (replaces version 1.00)

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Ralston Semi-Matt BW

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 1)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

Dangerous components:		
EC number: 918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%	>10–≤25%
Reg.nr.: 01-2119457273-39	aromatics	
	Alternative CAS number: 64742-48-9	
	🗞 Asp. Tox. 1, H304, EUH066	
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	>2.5–≤10%
Reg.nr.: 01-2119463258-33	aromatics	
	Alternative CAS number: 64742-47-8	
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	
CAS: 14807-96-6	Talc (Mg3H2(SiO3)4)	>2.5–≤10%
EINECS: 238-877-9	substance with a Community workplace exposure limit	
EC number: 920-114-2	Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	>2.5–≤10%
Reg.nr.: 01-2119459347-30	Alternative CAS number: 64742-46-7	
	🗞 Asp. Tox. 1, H304, EUH066	
CAS: 14808-60-7	Quartz (SiO2)	≥0–≤10%
EINECS: 238-878-4	substance with a Community workplace exposure limit	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

Consult doctor if symptoms persist.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Take off contaminated clothing.

Wash with water and soap.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* 7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Observe instructions for use / storage.

Requirements to be met by storerooms and receptacles:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions:

For information on the prevention of the release of synthetic polymer particles see Section 15

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
14807-96-6 Talc (Mg3H2(SiO3)4)		
WGW (Netherland)	Long-term value: 0.25 mg/m³	
	respirabel	
14808-60-7 Quartz (SiO2)		
BOELV (EU)	Long-term value: 0.1* mg/m³	
	*respirable fraction	
WGW (Netherland)	Long-term value: 0.075 mg/m³	
·	respirabele fractie	
DNEL		

	DNELs Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
ſ					
ľ	Oral	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)		
	Dermal	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)		
			208 mg/kg bw/24h (Workers)		
	Inhalative	DNEL Systemic; Long term	185 mg/m³ (Consumers)		
			871 mg/m³ (Workers)		

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

Hand protection




Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection





according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 4)

* 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid

Colour: Different according to colouring

Odour: Product specific
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range 154–193 °C (Hydrocarbons, C9-C11, n-alkanes,

isoalkanes, cyclics, <2% aromatics)

Flammability Flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.

Flash point: 53 °C

Auto-ignition temperature: 233 °C (Hydrocarbons, C10-C13, n-alkanes,

isoalkanes, cyclics, < 2% aromatics)

Decomposition temperature: Not determined. pH Not determined.

Viscosity:

Kinematic viscosity Not determined.

Dynamic at 20 °C: 1,263.64–1,492.9 mPas

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 0.5 hPa (Hydrocarbons, C10-C13, n-alkanes,

isoalkanes, cyclics, < 2% aromatics)

Density and/or relative density

Density at 20 °C:1.25–1.29 g/cm³Relative densityNot determined.Vapour densityNot determined.

9.2 Other information

Appearance:

Form: Viscous

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

 VOC (EC)
 22.02 %

 Solids content:
 77.7 %

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 5)

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes

Flammable liquids Flammable liquid and vapour.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Oxidising substances.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:				
Hydrocarl	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>5,000 mg/l (rat)		
Hydrocarl	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>5,000 mg/l (rat)		
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>5,266 mg/l (rat)		

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 6)

11.2 Information on other hazards

Endocrine disrupting properties	
None of the ingredients is listed.	

12 Ecological information

12.1 Toxicity

Aquatic toxicity:				
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)			
	1,000 mg/l /48h (daphnia)			
LL0	1,000 mg/l /96h (Oncorhynchus mykiss)			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
EL0	1,000 mg/l /48h (daphnia)			
EL50	>1,000 mg/l /72h (Pseudokirchneriella subcapitata)			
	1,000 mg/l /48h (daphnia)			
LL50	>1,000 mg/l /96h (Oncorhynchus mykiss)			
NOELR	100 mg/l /72h (Pseudokirchneriella subcapitata)			
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics				
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)			
	1,000 mg/l /48h (daphnia)			
LL0	87,556 mg/l /96h (Oncorhynchus mykiss)			
NOELR	1,000 mg/l /72h (Pseudokirchneriella subcapitata)			
	5 mg/l /21d (daphnia)			

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 7)

European waste catalogue

HP3 Flammable

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR UN1263 PAINT

IMDG PAINT IATA Paint

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA

14.5 Environmental hazards: Not applicable.

14.6 Special precautions for user Warning: Flammable liquids.

14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3
Tunnel restriction code D/E

Remarks: Exempted according to 2.2.3.1.5 (Viscous liquids)

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1263 PAINT, 3, III

(Contd. on page 9)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.10.2025 Version number 2.00 (replaces version 1.00) Revision: 08.10.2025

Trade name: Ralston Semi-Matt BW

(Contd. of page 8)

*15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior/exterior trim and cladding paints for wood and metal
 - · Solvent-borne coatings, Limit value: 300 g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 78

Additional information on Entry 78

Collect cleaning waters separately and forward them to appropriate disposal do not discharge into the sewer system

Collect product residues and contaminated packaging in closed containers do not rinse dispose of in accordance with legal requirements

Synthetic polymer microparticles

synthetic polymer microparticles

Type of polymer: 3902; Polymers of propylene or other olefins.

1.101%

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

REGULATION (EU) 2024/590 on substances that deplete the ozone layer

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

The product does not contain SVHC ≥ 0.1%

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to Regulation (EC) No 1907/2006, Article 31

Revision: 08.10.2025 Printing date 08.10.2025 Version number 2.00 (replaces version 1.00)

Trade name: Ralston Semi-Matt BW

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids On basis of test data

Version number of previous version: 1.00

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. of page 9)

^{*} Data compared to the previous version altered.