Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Ralston Endurance Primer BW

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Ralston Colour & Coatings B.V.
part of
Royal Van Wijhe Verf
Russenweg 14
8041 AL ZWOLLE
THE NETHERLANDS
+31(0)38 - 429 1100
info@ralstoncolour.com

1.4 Emergency telephone number:

NVIC
+31(0)88 755 8000
Only for the purpose of informing medical personnel in case of acute intoxications

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Additional information:

The full text of the classification and labelling elements mentioned is given in Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 1)

Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

3 Composition/information on ingredients

3.2 Mixtures

Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-48-9 Asp. Tox. 1, H304, EUH066	>10–≤25%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO_2) substance with a Community workplace exposure limit	>2.5–≤25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-47-8 Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	>2.5–≤10%
CAS: 14807-96-6 EINECS: 238-877-9	Talc ($Mg_3H_2(SiO_3)_4$) substance with a Community workplace exposure limit	>2.5–≤10%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO_2) fine fraction of crystalline sillica STOT RE 1, H372	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information:
Take affected persons out into the fresh air.
Keep warm, position comfortably and cover well.
Consult doctor if symptoms persist.

After inhalation:
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact:
Take off contaminated clothing.
Wash with water and soap.

After eye contact:
Rinse opened eye for several minutes under running water.
Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

(Contd. of page 2)

After swallowing:
If person is conscious, rinse out mouth.
Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters
Protective equipment: Wear fully protective suit.
Additional information
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities
Storage: Observe instructions for use / storage.
Requirements to be met by storerooms and receptacles: Store in a well-ventilated place. Keep cool.
Information about storage in one common storage facility: Store away from oxidising agents.
Further information about storage conditions:
Keep container tightly closed.

(Contd. on page 4)

(Contd. of page 3)

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
14808-60-7 Quartz (SiO2)	
BOELV (EU)	Long-term value: 0.1* mg/m³ *respirable fraction
WGW (Netherland)	Long-term value: 0.075 mg/m³ respirabele fractie
14807-96-6 Talc (Mg3H2(SiO3)4)	
WGW (Netherland)	Long-term value: 0.25 mg/m³ respirabel

DNELs		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)
Dermal	DNEL Systemic; Long term	125 mg/kg bw/24h (Consumers)
		208 mg/kg bw/24h (Workers)
Inhalative	DNEL Systemic; Long term	185 mg/m³ (Consumers)
		871 mg/m³ (Workers)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

Hand protection



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection



Tightly sealed goggles

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 4)

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information	
Physical state	Liquid
Colour:	Different according to colouring
Odour:	Product specific
Odour threshold:	Not determined
Melting point/freezing point:	Undetermined
Boiling point or initial boiling point and boiling range	154–193 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	Not determined
Upper:	Not determined
Flash point:	41 °C
Auto-ignition temperature:	233 °C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Decomposition temperature:	Not determined
pH	Not determined
Viscosity:	
Kinematic viscosity	Not determined
Dynamic at 20 °C:	1,221.59–1,444.5 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined
Vapour pressure at 20 °C:	0.5 hPa (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Density and/or relative density	
Density at 20 °C:	1.295–1.33 g/cm³
Relative density	Not determined
Vapour density	Not determined

9.2 Other information

Appearance:	
Form:	Viscous
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	22.16 %
Solids content:	78.1 %

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 5)

Change in condition

Evaporation rate Not determined

Information with regard to physical hazard classes

Flammable liquids Flammable liquid and vapour.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Oxidising substances.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 6)

12 Ecological information

12.1 Toxicity

Aquatic toxicity:	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
EL0	1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL0	1,000 mg/l /96h (Oncorhynchus mykiss)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
EL0	1,000 mg/l /48h (daphnia)
EL50	>1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL50	>1,000 mg/l /96h (Oncorhynchus mykiss)
NOELR	100 mg/l /72h (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR UN1263 PAINT

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 7)

IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class	3 Flammable liquids.
Label	3

14.4 Packing group

ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-E
Stowage Category	A

14.7 Maritime transport in bulk according to IMO instruments Not applicable

Transport/Additional information:

ADR

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
Remarks:	Exempted according to 2.2.3.1.5 (Viscous liquids)

IMDG

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

• Product subcategory: Interior/exterior trim and cladding paints for wood and metal

· Solvent-borne coatings, Limit value: 300 g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 8)

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors
None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.

REGULATION (EU) 2024/590 on substances that deplete the ozone layer

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57
The product does not contain SVHC ≥ 0.1%

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.10.2026 Version number 1.00 Revision: 25.10.2023

Trade name: Ralston Endurance Primer BW

(Contd. of page 9)

DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1