

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Ralston AQUA Satin Bioseries BW

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void.

Hazard pictograms Void.

Signal word Void.

Hazard statements Void.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one, adipohydrazide. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 1)

3 Composition/information on ingredients

3.2 Mixtures

Dangerous components:			
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg3H2(SiO3)4) substance with a Community workplace exposure limit	>2.5–≤10%	
CAS: 1071-93-8 EINECS: 213-999-5 Reg.nr.: 01-2119962900-36	adipohydrazide Aquatic Chronic 2, H411; Skin Sens. 1B, H317	≥0.25–<1%	
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg	<0.025%	
CAS: 55965-84-9 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Note: B Specific concentration limits: Skin Corr. 1C; H314:C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Sye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

Consult doctor if symptoms persist.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Take off contaminated clothing.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 2)

Wash with water and soap.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

For non-emergency personnel Keep people at a distance and stay on the windward side.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Observe instructions for use / storage.

Requirements to be met by storerooms and receptacles: No special requirements.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 3)

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

14807-96-6 Talc (Mg3H2(SiO3)4)

WGW (Netherland) Long-term value: 0.25 mg/m³
respirabel

55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one (3:1)

WGW (Netherland) Long-term value: 0.2 mg/m³

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

Hand protection



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection Goggles recommended during refilling

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid

Colour: Different according to colouring

Odour: Product specific
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range 100 °C (7732-18-5 water, distilled, conductivity or of

similar purity)

Flammability Not applicable.

(Contd. on page 5)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 4)

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.

Flash point: >100 °C

Decomposition temperature: Not determined.

pH at 20 °C 7–9

Viscosity:

Kinematic viscosity Not determined.

Dynamic at 20 °C: 2,853.73–3,712.4 mPas

Solubility

water: Fully miscible.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or of

similar purity)

Density and/or relative density

Density at 20 °C:1.28–1.3 g/cm³Relative densityNot determined.Vapour densityNot determined.

9.2 Other information

Appearance:

Form: Viscous

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

VOC (EC) 0.23 % **Solids content:** 53.2 %

Change in condition

Evaporation rate Not determined.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 5)

LD/LC50 values relevant for classification:			
2634-33-5 1,2-benzisothiazol-3(2H)-one			
Oral	LD50	450 mg/kg (ATE)	
55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-			
3- one (3:1)			
Inhalative LC50/4 h 0.31 mg/l (rat)			

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:		
2634-33-5 1,2-benzisothiazol-3(2H)-one		
EC50	2.9 mg/l /48h (daphnia)	
ErC50	0.11 mg/l /72h (Pseudokirchneriella subcapitata)	
LC50	2.15 mg/l /96h (Oncorhynchus mykiss)	
NOEC	0.0403 mg/l /72h (Pseudokirchneriella subcapitata)	
55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-		
3- one (3:1)		
EL50	0.018 mg/l /72h (algae)	

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 6)

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

14.1 UN number or ID number

ADR, IMDG, IATA Not regulated.

14.2 UN proper shipping name

ADR, IMDG, IATA Not regulated.

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Not regulated.

14.4 Packing group

ADR, IMDG, IATA

Not regulated.

14.5 Environmental hazards:

Not applicable.

Not applicable.

14.7 Maritime transport in bulk according to

IMO instruments Not applicable.
UN "Model Regulation": Not regulated.

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior/exterior trim and cladding paints for wood and metal
 - · Water-borne coatings, Limit value: 130 g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 8)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 7)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

REGULATION (EU) 2024/590 on substances that deplete the ozone layer

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

The product does not contain SVHC ≥ 0.1%

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

11004	T 1 16 11 1
H301	Toxic if swallowed.

- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.09.2025 Version number 1.00 Revision: 23.09.2025

Trade name: Ralston AQUA Satin Bioseries BW

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2