

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

### 1 Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** Ralston ExtraTex Satin 20 W/BW

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Paint

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

Ralston Colour & Coatings B.V.

part of

Royal Van Wijhe Verf

Russenweg 14

8041 AL ZWOLLE

THE NETHERLANDS

+31(0)38 - 429 1100

msds@ralstoncolour.com

#### 1.4 Emergency telephone number:

NVIC

+31(0)88 755 8000

Only for the purpose of informing medical personnel in case of acute intoxications

### 2 Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

The product is not classified, according to the CLP regulation.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008** Void.

**Hazard pictograms** Void.

**Signal word** Void.

**Hazard statements** Void.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

(Contd. on page 2)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 1)

**3 Composition/information on ingredients**

**3.2 Mixtures**

<b>Dangerous components:</b>		
CAS: 1317-65-3 EINECS: 215-279-6	Limestone (calcium carbonate) substance with a Community workplace exposure limit	>10–≤25%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10	propylidyntrimethanol ⚠ Repr. 2, H361fd	≥0–≤2.5%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60	1,2-benzisothiazol-3(2H)-one ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<0.05%
CAS: 55965-84-9 EC number: 611-341-5 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071 Note: B Specific concentration limits: Skin Corr. 1C; H314:C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025–<0.0015%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures**

**4.1 Description of first aid measures**

**General information:**

Take affected persons out into the fresh air.  
Keep warm, position comfortably and cover well.  
Consult doctor if symptoms persist.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Take off contaminated clothing.  
Wash with water and soap.

**After eye contact:**

Rinse opened eye for several minutes under running water.

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 2)

Remove contact lenses, if present and easy to do. Continue rinsing.

**After swallowing:**

If person is conscious, rinse out mouth.

Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing agents:**

Use fire extinguishing methods suitable to surrounding conditions.

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**

**Protective equipment:** Wear fully protective suit.

**Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### 6 Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

**For non-emergency personnel** Keep people at a distance and stay on the windward side.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

**Information about fire - and explosion protection:** No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:** Observe instructions for use / storage.

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:**

Keep container tightly closed.

(Contd. on page 4)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 3)

Store in a well-ventilated place. Keep cool.

**7.3 Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

**8.1 Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>		
<b>1317-65-3 Limestone (calcium carbonate)</b>		
WGW (Netherland)	Long-term value: 10 mg/m <sup>3</sup> zie bijl. 3	
<b>77-99-6 propylidynetrimethanol</b>		
WGW (Netherland)	Long-term value: 5 mg/m <sup>3</sup>	
<b>55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)</b>		
WGW (Netherland)	Long-term value: 0.2 mg/m <sup>3</sup>	
<b>DNELs</b>		
<b>77-99-6 propylidynetrimethanol</b>		
Oral	DNEL Systemic; Long term	0.34 mg/kg bw/24h (Consumers)
Dermal	DNEL Systemic; Long term	0.34 mg/kg bw/24h (Consumers)
		0.94 mg/kg bw/24h (Workers)
Inhalative	DNEL Systemic; Long term	0.58 mg/m <sup>3</sup> (Consumers)
		3.3 mg/m <sup>3</sup> (Workers)

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:** Wash hands before breaks and at the end of work.

**Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

**Hand protection**



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye/face protection** Goggles recommended during refilling

**9 Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Physical state**

Fluid

(Contd. on page 5)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 4)

<b>Colour:</b>	Different according to colouring
<b>Odour:</b>	Product specific
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Undetermined.
<b>Boiling point or initial boiling point and boiling range</b>	100 °C (7732-18-5 water, distilled, conductivity or of similar purity)
<b>Flammability</b>	Not applicable.
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Flash point:</b>	Not applicable.
<b>Decomposition temperature:</b>	Not determined.
<b>pH at 20 °C</b>	8–9
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>Dynamic at 20 °C:</b>	1,592.43–1,897.6 mPas
<b>Solubility</b>	
<b>water:</b>	Fully miscible.
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	23 hPa (7732-18-5 water, distilled, conductivity or of similar purity)
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.46–1.49 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Viscous
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>Solvent content:</b>	
<b>VOC (EC)</b>	0.05 %
<b>Solids content:</b>	65.5 %
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.

**10 Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability** The product is stable.

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 6)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 5)

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>		
<b>1317-65-3 Limestone (calcium carbonate)</b>		
Oral	LD50	>5,000 mg/kg (rat)
<b>77-99-6 propylidynetrimethanol</b>		
Oral	LD50	14,100 mg/kg (rat)
<b>55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)</b>		
Inhalative	LC50/4 h	0.31 mg/l (rat)

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

<b>77-99-6 propylidynetrimethanol</b>	
Developmental and reproductive toxicity	(rat) Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments., Suspected of damaging fertility. Suspected of damaging the unborn child.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

<b>Endocrine disrupting properties</b>
None of the ingredients is listed.

**12 Ecological information**

**12.1 Toxicity**

<b>Aquatic toxicity:</b>	
<b>1317-65-3 Limestone (calcium carbonate)</b>	
EC50	>1,000 mg/l /48h (daphnia) >200 mg/l /72h (Desmodesmus subspicatus)
LC50	>10,000 mg/l /96h (Oncorhynchus mykiss)

(Contd. on page 7)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 6)

<b>2634-33-5 1,2-benzisothiazol-3(2H)-one</b>	
EC50	2.9 mg/l /48h (daphnia)
ErC50	0.11 mg/l /72h (Pseudokirchneriella subcapitata)
LC50	2.15 mg/l /96h (Oncorhynchus mykiss)
NOEC	0.0403 mg/l /72h (Pseudokirchneriella subcapitata)
<b>55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)</b>	
EL50	0.018 mg/l /72h (algae)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Additional ecological information:**

**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**13 Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**14 Transport information**

**14.1 UN number or ID number**

**ADR, IMDG, IATA** Not regulated.

**14.2 UN proper shipping name**

**ADR, IMDG, IATA** Not regulated.

**14.3 Transport hazard class(es)**

**ADR, ADN, IMDG, IATA**

**Class** Not regulated.

**14.4 Packing group**

**ADR, IMDG, IATA** Not regulated.

**14.5 Environmental hazards:** Not applicable.

**14.6 Special precautions for user** Not applicable.

**14.7 Maritime transport in bulk according to**

**IMO instruments** Not applicable.

(Contd. on page 8)



**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 7)

**UN "Model Regulation":**

Not regulated.

**15 Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Directive 2004/42/EC**

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior matt walls and ceilings (Gloss < 25@60°)
- Water-borne coatings, Limit value: 30 g/l

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

**Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.04.2024

Version number 1.00

Revision: 25.10.2023

**Trade name:** Ralston ExtraTex Satin 20 W/BW

(Contd. of page 8)

EUH071 Corrosive to the respiratory tract.

### **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2